

TECHNICAL SPECIFICATION

Machine output : Upto 200 to 300 cartons per hour depending on operator's skill, carton size and packing material

Packing material : Bi-axially oriented polypropylene (BOPP) Heat Sealable

Packaging Film Cutting: Automatic

Heater temperature : stability ± 1 to 2° of the set value \

Temperature Range : Minimum +40 to maximum +220 C

Packaging Film Thickness: 20 TO 40 Micron, must be suitable for over wrapping

Maximum Film Width : 250 mm

Maximum Roll Dia. : 250 mm

Voltage : 230VAC/60Hz

Power consumption : Approx. 300 Watt

Net Weight : 55kg

Machine Dimensions : 400 W x 300 L x 430 H. (Approx.).



Registered Office Address :

Unit No-11, Shiva Industrial Estate, Lake Road,
Near TATA Power, Bhandup (W), Mumbai 400078
Web : www.shrutiflexipack.com

Factory Address :

Plot No. B-49, MIDC Road, Behind Reliable Plaza,
Near Chinchapada, TTC Ind. Area,
Airoli, Thane Belapur Road, Navi Mumbai 400708
Phone : +91-9619909581 / +91-7506129084
E-mail : marketing@shrutiflexipack.com
Web : www.shrutiflexipack.com


SHRUTI
FLEXIPACK PVT. LTD



OVERWRAPPING MACHINE-SEMI AUTOMATIC MODEL

DESCRIPTION OF OPERATION:

The Unit consists of a base plate machine construction in 3 mm mild steel machine frame and roll mounting assembly. For best performance auto roll cutting to desired length of the packing material and auto topping of roll is provided in this machine. . The sealing heater is fitted on the base plate just below the cutting assembly; it makes very easy to seal the edges immediately after cutting. The sealing bar is fitted with pencil heaters. The temperature is controlled with electronic temperature controller. Machine is controlled with microprocessor, for every cutting signal, one foot switch signal is required. Triggering system give better performance and increase heater life.